

4G LTE/CELLULAR

ONBOARD SMD SHRAPNEL ANTENNA



824-960 MHz | 1710-2690 MHz

Dimensions: 26.00 x 14.78 x 4.50 mm

Clearance Area: 30.5 x 30.5 mm



ADCM001

PN: M01-X02614M4G1





Table of Contents

1 FEATURES & BENEFITS	1
2 APPLICATIONS.....	1
3 ORDER INFORMATION	1
4 REFERENCE GUIDE.....	2
5 EVALUATION BOARD WITH ANTENNA	2
6 MATCHING NETWORK	3
7 RECOMMENDED FOOTPRINT AND LAYOUT.....	4
8 ELECTRICAL PERFORMANCE.....	5
8.1 VSWR and Return Loss (dB).....	5
8.2 Gain (dBi) and Total Efficiency (%).....	6
8.3 2D Radiation Patterns (824-960 MHz)	8
8.4 2D Radiation Patterns (1710-2690 MHz).....	9
9 SOLDERING CONDITIONS	10
10 PACKAGING.....	12
10.1 Optimal Storage Conditions for Packaged Reels	12
10.2 Packagings and Dimensions (Unit: mm).....	13
11 ANTENNA CERTIFICATION	14
12 WELCOME ALL ANTENNA OEM/ODM PROJECTS	15

www.aboosty.com

The materials provided herein, which are intended for illustration purposes only, are believed to be reliable and correct. However, no responsibility is further assumed for inaccuracies or incompleteness, and all such information shall be entirely at the user's risk. All information is subject to change without prior notice.

Copyright © 2024 ShenZhen MyAntenna RF Technology Co., Ltd. All Rights Reserved.




1 FEATURES & BENEFITS

- Low Profile
- Light Weight
- Easy to Integrate
- Intended for SMD Mounting
- Reduced Cost and Time-to-Market

2 APPLICATIONS

- 4G LTE network connectivity for smartphones and tablets
- Wireless Payment Terminals like POS machines
- Internet of Things (IoT) Devices
- Wearable Devices
- Industrial and Commercial Equipment
- Routers and Gateway Devices

	
Items	Dimensions (mm)
Length	26.00±0.1
Width	14.78±0.1
Thickness	4.50±0.1

3 ORDER INFORMATION

Product Name	4G LTE/CELLULAR OnBoard SMD Shrapnel Antenna
Model	ADCM001
Part No.	M01-X02614M4G1
Dimensions	26.00 x 14.78 x 4.50 mm
Weight	1.1 g
Mounting	SMT
Packaging	Tape & Reel
MOQ	500 pcs/reel


4 REFERENCE GUIDE

Technical Features	824-960 MHz	1710-2690 MHz
Max VSWR	3.69:1	2.49:1
Max Efficiency	77.58%	
Max Return Loss	-0.20 dB	
Peak Gain	Up to 2.24 dBi (Typ)	
Max Input Power	2 Watts CW	
Polarization	Linear	
Input Impedance	50 Ω	
Operating Temperature	-40°C to +80°C	
Relative Humidity	10 to 70%	


All data were measured in free space and on a reference wground plane of 130 mm length, 55 mm width, and 1.0 mm thickness. Application data might vary.

5 EVALUATION BOARD WITH ANTENNA

The evaluation board provides operation at 600-3000 MHz.
Evaluation Board dimension: 133.0 x55.0 x 1.0 mm
Clearance Area: 30.5 x 30.5 mm




Top View




Back View

6 MATCHING NETWORK



7 RECOMMENDED FOOTPRINT AND LAYOUT




Tag Number	Value	Brand	PN
S1	RES SMD 0402 0R $\pm 1\%$	UniOhm	D03-0100010000
S2	NC	NC	NC
S3	NC	NC	NC

8 ELECTRICAL PERFORMANCE

© Note


All data displayed in Chapter 8 were measured in free space and on a reference ground plane of 130 mm length, 55 mm width, and 1.0 mm thickness.

8.1 VSWR and Return Loss (dB)





8.2 Gain (dBi) and Total Efficiency (%)




Antenna Data					
Freq (MHz)	Gain (dBi)	Efficiency (%)	Freq (MHz)	Gain (dBi)	Efficiency (%)
824	-2.98	30.12	904	-1.74	33.23
834	-3.20	29.25	914	-1.73	32.79
844	-2.95	29.74	924	-1.69	32.41
854	-2.89	30.86	934	-1.78	31.73
864	-2.83	30.15	944	-1.70	31.53
874	-2.34	32.09	954	-1.74	31.08
884	-2.30	32.09	960	-1.71	30.62
894	-2.10	31.66			




Freq (MHz)	Gain (dBi)	Efficiency (%)	Freq (MHz)	Gain (dBi)	Efficiency (%)
1710	-3.31	23.52	2230	0.48	66.47
1750	-0.03	31.91	2270	0.09	61.08
1790	0.89	36.36	2310	0.05	59.35
1830	1.86	43.31	2350	0.11	58.77
1870	2.41	54.66	2390	0.39	59.69
1910	2.46	60.41	2430	0.26	60.27
1950	1.87	67.53	2470	0.48	61.39
1990	2.12	73.36	2510	1.52	65.57
2030	1.94	75.13	2550	1.61	64.90
2070	2.24	74.47	2590	1.40	61.89
2110	1.65	72.63	2630	1.64	60.89
2150	1.80	77.58	2670	1.43	59.50
2190	1.16	72.04	2690	1.40	61.03

8.3 2D Radiation Patterns (824-960 MHz)



8.4 2D Radiation Patterns (1710-2690 MHz)






9 SOLDERING CONDITIONS

This antenna is suitable for lead free soldering.
Below shows the temperature profile for soldering.

Setpoints (Celsius degree)								
Temperature Zones	1	2	3	4	5	6	7	8
Upper-Temperature Zone	120	160	175	180	190	250	255	250
Lower Temperature Zone	120	160	175	180	190	250	255	250
Conveyor Speed (cm/min): 65.00								













PWI= 142%	Preheat 40 to 150 °C		Soak Time 150 to 180°C		Reflow Time /217°C		Peak Temperature		Slope 2 (150-217°C)		Slope 3 (217-250°C)	
	74.78	-51%	69.58	-26%	100.01	133%	251.15	107%	1.37	37%	0.77	-39%
	76.94	-44%	70.75	-23%	102.55	142%	251.56	109%	1.41	41%	0.81	-35%
	75.26	-49%	69.53	-26%	99.40	131%	250.66	104%	1.37	37%	0.75	-40%
	73.18	-56%	70.44	-24%	101.64	139%	251.34	108%	1.37	37%	0.76	-39%
	71.55	-61%	71.62	-21%	100.41	135%	250.73	104%	1.34	34%	0.86	-31%
Temperature Differences	5.39		2.09		3.15		0.90		0.07		0.11	

Process Limits:			
Solder Paste:	Lead-Free		
Statistical Name	Lower Limit	Upper Limit	Unit
Slope 2 (Target=1.0) Between 150.0 and 217.0 (Time interval for slope calculation = 20 seconds)	0	2	°C/sec
Slope 3 (Target=1.3) Between 217.0 and 250.0 (Time interval for slope calculation = 20 seconds)	0	2.5	°C/sec
Preheat Time 40-150°C	60	120	sec
Soak Time 150-180°C	40	120	sec
Time Above Reflow -217°C	30	90	sec
Peak Temperature	217	250	°C

© Note

Please select a nozzle from No.500 to 509 according to the shape and size of the mounted component.

No.	500	501	502	503	504	505	506	507	508C	509
Shape										
Inner Diameter	1.0x0.5mm	0.7x0.4mm	φ0.7mm	φ1.0mm	φ1.5mm	φ3.5mm	φ5.0mm	φ8.5mm	φ9.5mm	0.4×0.2mm
Outside Diameter	2xφ0.4mm	φ0.25mm	φ0.4mm	φ0.6mm	φ1.0mm	φ1.7mm	φ3.2mm	φ5.0mm	φ8.0mm	φ0.1mm

1. The recommended SMT nozzle size is larger than 505#;
2. The recommended solder paste thickness is above 0.12mm.



10 PACKAGING

10.1 Optimal Storage Conditions for Packaged Reels


Temperature	-5°C to 40°C
Humidity	Less than 70% RH
Shelf life	18 months
Storage place	Away from corrosive gas and direct sunlight
Packaging	Reels should be stored in unopened sealed manufacturer's plastic packaging.

© **Note**

Storage of open reels of antennas is not recommended due to possible oxidation of pads on antennas. If short-term storage is necessary, then it is highly recommended that the bag containing the antenna reel is re-sealed and stored in like storage conditions as in the above table.



10.2 Packagings and Dimensions (Unit: mm)





11 ANTENNA CERTIFICATION

RoHS Approval	Compliant [2011/65/EU&2015/863]
REACH Approval	Conform or declared [(EC)1907/2006]
Hazardous material regulation conformance: A certificate of conformance is available upon request. Feel free to consult us for details.	



12 WELCOME ALL ANTENNA OEM/ODM PROJECTS

About ABOOSTY



10+ years in antenna R&D, production, and OEM/ODM



House of Aboosty: 450,000 units annual output capacity



Factory directly competitive price



Industry-leading quality levels



Professional team-work & support



Quick price and lead time estimation

Why Choose ABOOSTY



Innovative and patented design solutions



Full terminal devices anechoic chamber test



Co-location with its custom



Competitive price



Strict inspection




Prompt reply within 24h

What We Provide

OEM/ODM Services	
Light Customization	Deep Customization
<ul style="list-style-type: none"> • Logo • Packaging • Cables&Connectors 	<ul style="list-style-type: none"> • In-depth tailoring for specific applications • Functional enhancements • Environmental adaptations • Vertical certifications • ...

Custom Process

Light Customization Process





Deep Customization Process

